

Product Information					
Construction	Thickness	Wear Layer	Length	Width	Underlayment
SPC Herringbone Vinyl	6mm	0.5mm 20 mil	28-3/4" 730mm	5-3/4" 146mm	Including 1.5mm Cork Underlayment
Finish	The Look	Residential Warranty	Commercial Warranty	Locking System	Installation Instruction
2-pass UV cured Urethane Finish	Ultra Realistic	30-Year	12-Year	Välinge® 5G Locking	Please refer to Installation Instruction, Care and Maintenance Guide



- FloorScore Certified - no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.

Testing		
Classification	Method	Result
Class	ASTM F1700-18	Class III, Type B - Embossed
Residual Indentation	ASTM F1914-17	Pass
Slip Resistance	ASTM C1028-07	Dry: 0.84; Wet: 0.77
Static Load	ASTM F970-17	0.07mm
Dimensional Stability	ASTM F2199-09	Pass
Resistant to Heat	ASTM F1514-03	Pass
Resistant to Chemicals	ASTM F925-13	Pass
Resistant to Light	ASTM F1515-15	Pass
Critical Radiant Flux	ASTM E648-17	Class I
IIC	ASTN E492-09	71
STC	ASTM E90-09	71

Packaging Information

	Length	Width	Thickness	Sq. ft.	Weight
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)
Plank	730	146	6		
Plank Carton	735	150	110	20.7	40

Pallet Information

	Dimension	Volume	# of carton	Sq. ft.	Weight
	(mm)	(m ³)	per Pallet	/pallet	(lb.)
Plank Pallet	740x900x980	0.65	48	993.6	1920