


**Features**

- Välinge® 5Gi locking system makes it easy to install. Can be installed for 80 linear feet or 25 meters without a transition moulding.
- 100% waterproof, ideal for 3 season cottages and homes with kids and pets.
- High density core is ultra-stable and impervious to water damage, making it ideal for light commercial and heavy residential traffic.
- Armor Care technology: 2-pass UV cured urethane finish that is exceptionally stain and scratch resistant.
- FloorScore Certified - no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.



**Product Information**

<b>Product Line</b>	SolidCore Luxury Vinyl Flooring
<b>Construction</b>	SPC (Stone Polymer Composite) vinyl
<b>Dimension</b>	5mm (T) x 180mm (W) x 1220mm (L)
<b>Underlayment</b>	1mm IXPE underlayment
<b>Wear Layer Thickness</b>	0.3mm (12 mil)
<b>Finish</b>	2-pass UV cured Urethane Finish
<b>Installation</b>	Floating installation by clicking the end joints together. Please refer to Installation Instruction
<b>Warranty</b>	30 Year Residential and 10 Year Commercial Warranty

**Testing**

Classification	Method	Result
Class	ASTM F1700	Class III, Type B - Embossed
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm
ΔIIC	ASTM E2179-03	25
IIC	ASTM E492-09	71
STC	ASTM E90-09	71
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot
Resistant to Chemicals	ASTM F925	Pass: Not affected
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens
Reaction to Fire	EN13501-1	Class B fl-s1
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm <sup>2</sup>
Concentration of Dibutyl Phthalate	ISO 16000	<1 µg/m <sup>3</sup> after 28 days
Concentration of Diethylhexyl Phthalate	ISO 16000	<1 µg/m <sup>3</sup> after 28 days
Flexibility	EN435	No Damage

**Packaging Information**

	Length (mm)	Width (mm)	Thickness (mm)	Sq. ft. per Carton	Weight (lb. per carton)
<b>Plank</b>	1220	180	5		
<b>Plank Carton</b>	1230	190	65	28.4	47

**Pallet Information**

	Length (mm)	Width (mm)	Height (mm)	Volume (m <sup>3</sup> )	# of carton per Pallet	Sq. ft. /pallet	Weight (lb.)
<b>Plank Pallet</b>	1245	965	600	0.72	45	1278	2115