


Luxury Vinyl Flooring

SolidCore Ultra Collection

Features

- I4F locking system makes it easy to install. Can be installed for 80 linear feet or 25 meters without a transition moulding.
- 100% waterproof, ideal for 3 season cottages and homes with kids and pets.
- High density core is ultra-stable and impervious to water damage, making it ideal for light commercial and heavy residential traffic.
- Armor Care technology: 2-pass UV cured urethane finish that is exceptionally stain and scratch resistant.
- FloorScore Certified no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.





The world's easiest flooring installation system



Product Information	
Product Line	SolidCore Ultra Luxury Vinyl Flooring
Construction	SPC (Stone Polymer Composite) vinyl
Dimension	5mm (T) x 229mm (W) x 1570mm (L)
Underlayment	1mm IXPE underlayment
Wear Layer Thickness	0.5mm (20 mil)
Finish	2-pass UV cured Urethane Finish
Installation	Floating installation by clicking the end joints together. Please refer to Installation Instruction
Warranty	Lifetime Residential, 15-Year Commercial Warranty

Testing					
Classification	Method	Result			
Class	ASTM F1700	Class III, Type B - Embossed			
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71			
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm			
ΔΙΙC	ASTM E2179-03	25			
IIC	ASTM E492-09	71			
STC	ASTM E90-09	71			
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot			
Resistant to Chemicals	ASTM F925	Pass: Not affected			
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss			
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens			
Reaction to Fire	EN13501-1	Class B fl-s1			
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm ²			
Concentration of Dibutyl Phthalate	ISO 16000	<1 μg/m³ after 28 days			
Concentration of Diethylhexyl Phthalate	ISO 16000	<1 μg/m³ after 28 days			
Flexibility	EN435	No Damage			

Packaging Information								
	Length	Width	Thickness	Sq. ft.	Weight			
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)			
Plank	1570	225	5					
Plank Carton	1580	230	40	31	51			

Pallet Information								
	Length	Width	Height	Volume	# of carton	Sq. ft.	Weight	
	(mm)	(mm)	(mm)	(m³)	per Pallet	/pallet	(lb.)	
Plank Pallet	1580	920	600	0.87	52	1612	2652	