

Product Information

Construction	Thickness	Wear Layer	Length	Width	Underlayment
SPC Vinyl	5.5mm	0.3mm 12 mil	48" 1220mm	Plank: 7" 180mm	Including 1mm IXPE Underlayment
Finish	The Look	Residential Warranty	Commercial Warranty	Locking System	Installation Instruction
2-pass UV cured Urethane Finish	Ultra Realistic	30-Year	10-Year	Välinge® 5G Locking	Please refer to Installation Instruction, Care and Maintenance Guide



- FloorScore Certified - no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.

Testing		
Classification	Method	Result
Class	ASTM F1700	Class III, Type B - Embossed
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm
ΔIIC	ASTM E2179-03	25
IIC	ASTM E492-09	71
STC	ASTM E90-09	71
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot
Resistant to Chemicals	ASTM F925	Pass: Not affected
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens
Reaction to Fire	EN13501-1	Class B fl-s1
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm ²
Concentration of Dibutyl Phthalate	ISO 16000	<1 µg/m ³ after 28 days
Concentration of Diethylhexyl Phthalate	ISO 16000	<1 µg/m ³ after 28 days
Flexibility	EN435	No Damage