


Product Information					
Construction	Thickness	Wear Layer	Length	Width	Underlayment
WPC Vinyl	7mm	0.5mm 20 mil	48" 1220mm	7" 180mm	Including 1mm IXPE Underlayment
Finish	The Look	Residential Warranty	Commercial Warranty	Locking System	Installation Instruction
2-pass UV cured Urethane Finish	Ultra Realistic	30-Year	12-Year	Välinge® 5G Locking	Please refer to Installat: Instruction, Care and Maintenance Guide



- No traces of VOCs, phthalate-free, no formaldehyde off-gassing, and 100% recyclable.

Testing		
Classification	Method	Result
Class	ASTM F1700	Class III, Type B - Embossed
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm
ΔIIC	ASTM E2179-03	23
IIC	ASTM E492-09	72
STC	ASTM E90-09	71
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot
Resistant to Chemicals	ASTM F925	Pass: Not affected
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens
Reaction to Fire	EN13501-1	Class B fl-s1
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm ²
Concentration of Dibutyl Phthalate	ISO 16000	<1 µg/m ³ after 28 days
Concentration of Diethylhexyl Phtha	ISO 16000	<1 µg/m ³ after 28 days
Flexibility	EN435	No Damage

Packaging Information

	Length	Width	Thickness	Sq. ft.	Weight
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)
Plank	1220	180	7		
Plank Carton	1237	192	74	23.64	35

Pallet Information

	Dimension	Volume	# of carton	Sq. ft.	Weight
	(mm)	(m ³)	per Pallet	/pallet	(lb.)
Plank Pallet	1240 x 960 x 1062	1.26	65	1536.6	2275