


Features

- FloorScore certified no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.
- Patented Välinge® 5G Joint is strongest on the market, and proven to effectively reduce the chances of gapping
- Painted bevels add to a more realistic appearance. Made to closely resemble grout line on tiles
- Built-in antimicrobial cork underlayment has superior sound absorption and thermal insulation properties
- Wear layer is enhanced with Armor Care technology, making it exceptionally stain and scratch resistant

Armor Care anti-stain and scratch resistant coating



Ultra-thick 0.5mm (20mil) wear layer Beautiful looks with rich texture

High density composite core, waterproof Cork underlayment - antimicrobial and protects against mould and mildew

Välinge 5G® locking system



Product Information					
Product Line	SureWood Luxury Vinyl Flooring				
Construction	WPC (wood polymer composite) vinyl				
Dimension	King size:				
Underlayment	1.5mm antimicrobial cork underlayment				
Wear Layer Thickness	0.5mm (20 mil)				
Finish	2-pass UV cured Urethane Finish				
Installation	Floating installation by clicking the end joints together. Please refer to Installation Instruction				
Warranty	Lifetime Residential and 12 Year Commercial Warranty				

Testing						
Classification	Method	Result				
Class	ASTM F1700	Class III, Type B - Embossed				
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71				
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm				
ΔΙΙΟ	ASTM E2179-03	23				
IIC	ASTM E492-09	72				
STC	ASTM E90-09	71				
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot				
Resistant to Chemicals	ASTM F925	Pass: Not affected				
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss				
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens				
Reaction to Fire	EN13501-1	Class B fl-s1				
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm ²				
Concentration of Dibutyl Phthalate	ISO 16000	<1 µg/m³ after 28 days				
Concentration of Diethylhexyl Phthalate	ISO 16000	<1 µg/m³ after 28 days				
Flexibility	EN435	No Damage				



WPC Flooring SureWood Plus Collection

Packaging Information								
	Length	Width	Thickness	Sq. ft.	Weight			
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)			
King Size	1522	225	8					
King Size Carton	1535	235	51	22.2	36			

Pallet Information							
	Length	Width	Height	Volume	# of carton	Sq. ft.	Weight
	(mm)	(mm)	(mm)	(m³)	per Pallet	/pallet	(lb.)
King Size Pallet	1535	940	870	1.26	60	1332	2160