

Product Information

| Construction | Thickness | Wear Layer | Width & Length | | Underlayment |
|---------------------------------|-----------------|----------------------|--|---------------------|--|
| SPC Vinyl | 5.5mm | 0.5mm 20 mil | 7" x 48" 180mm x 1220mm 8-7/8" x 60" 1522mm | | Including 1mm IXPE Underlayment |
| Finish | The Look | Residential Warranty | Commercial Warranty | Locking System | Installation Instruction |
| 2-pass UV cured Urethane Finish | Ultra Realistic | Lifetime | 15-Year | Välinge® 5G Locking | Please refer to Installation Instruction, Care and Maintenance Guide |



- FloorScore Certified - no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.

Testing

| Classification | Method | Result |
|------------------------|---------------|------------------------------|
| Class | ASTM F1700-18 | Class III, Type B - Embossed |
| Residual Indentation | ASTM F1914-17 | Pass |
| Slip Resistance | ASTM C1028-07 | Dry: 0.84; Wet: 0.77 |
| Static Load | ASTM F970-17 | 0.07mm |
| Dimensional Stability | ASTM F2199-09 | Pass |
| Resistant to Heat | ASTM F1514-03 | Pass |
| Resistant to Chemicals | ASTM F925-13 | Pass |
| Resistant to Light | ASTM F1515-15 | Pass |
| Critical Radiant Flux | ASTM E648-17 | Class I |
| ΔIIC | ASTM E2179-03 | 25 |
| IIC | ASTN E492-09 | 71 |
| STC | ASTM E90-09 | 71 |