

Product Information					
Construction	Thickness	Wear Layer	Width & Length		Underlayment
SPC Vinyl	5.5mm	0.5mm   20 mil	7" x 48"   180mm x 1220mm 8-7/8" x 60"   1522mm		Including 1mm IXPE Underlayment
Finish	The Look	Residential Warranty	Commercial Warranty	Locking System	Installation Instruction
2-pass UV cured Urethane Finish	Ultra Realistic	Lifetime	15-Year	Välinge® 5G Locking	Please refer to Installation Instruction, Care and Maintenance Guide



- FloorScore Certified - no traces of VOCs, phthalate-free, no formaldehyde off-gassing, and are 100% recyclable.

Testing		
Classification	Method	Result
Class	ASTM F1700-18	Class III, Type B - Embossed
Residual Indentation	ASTM F1914-17	Pass
Slip Resistance	ASTM C1028-07	Dry: 0.84; Wet: 0.77
Static Load	ASTM F970-17	0.07mm
Dimensional Stability	ASTM F2199-09	Pass
Resistant to Heat	ASTM F1514-03	Pass
Resistant to Chemicals	ASTM F925-13	Pass
Resistant to Light	ASTM F1515-15	Pass
Critical Radiant Flux	ASTM E648-17	Class I
ΔIIC	ASTM E2179-03	25
IIC	ASTN E492-09	71
STC	ASTM E90-09	71

**Product Spec Sheet**  
**SolidCore Premier5G Collection**



Packaging Information					
	Length	Width	Thickness	Sq. ft.	Weight
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)
<b>7" x 48" Plank</b>	1220	180	5.5		
<b>8-7/8" x 60" Plank</b>	1522	225	5.5		
<b>7" x 48" Carton</b>	1230	190	60	23.7	47
<b>8-7/8" x 60" Carton</b>	1530	230	36	22.2	45

Pallet Information					
	Dimension	Volume	# of carton	Sq. ft.	Weight
	(mm)	(m <sup>3</sup> )	per Pallet	/pallet	(lb.)
<b>7" x 48" Pallet</b>	1230 x 950 x 685	0.80	45	1066.5	2115
<b>8-7/8" x 60" Pallet</b>	1530 x 920 x 478	0.67	52	1154.4	2340